

2. Intended use/es:

1. Unique identification code of product type:



Page 1 / 3 DoP 011 Version 6.0

DECLARATION OF PERFORMANCE No. 011

Wire nail, plain, D-head, paper collated, diameter 3.1 mm

Used for structural timber products

3.	Manufacturer:
	Pintos Oy
	Pysäkintie 12
	27510 Eura
	FINLAND
5.	System/s of AVCP:
	System 3
6 a	. Harmonised standard:
	EN 14592:2008+A1:2012
	Notified body/ies:
	VTT Expert Services Oy, identification number 0537,
	Initial type Testing Report No. VTT-S-07083-13
	Factory production control (FPC) system is maintained under the responsibilities of the manufacturer.





Page 2 / 3 DoP 011 Version 6.0

7. Declared performance/s:

Harmonized technical specification:

Dimensions:

EN 14592:2008+A1:2012

Material:

Characteristics tensile strength of wire: min ≥ 800 N/mm² according to EN

14592:2008+A1:2012

Bright / Hot dip zinc coated: EN 16120

Coating:

Hot dip zinc coating:

Zinc layer thickness ≥ 49 µm, Service Class 3 according to EN 1995-1-1

Angle of collation:

Paper collated: 34° Essential characteristics:

EN 14592:2008+A1:2012

HOT DIP ZINC COATING, Durability i.e corrosion protection Z350 Service Class 3

Name	Dimensions	Head cross-	Characteristic	Characteristic	Characteristic	Characteristic
	diameter x	sectional area	yield moment	withdrawal	head pull-	tensile
	length	A _h	$M_{v,k}$	parameter ^{a)}	through	capacity
	d x l	[mm²]	[Nmm]	$f_{ax,k}$	parameter ^{a)}	$f_{tens,k}$
	[mm]			[N/mm ²]	$f_{head,k}$	[kN]
					[N/mm²]	
3,1 x 90	2,98 x 89	30,2	4170	2,45	18,81	NPD ^{b)}

BRIGHT, Durability i.e corrosion protection Service Class 1

Nam	e	Dimensions	Head cross-	Characteristic	Characteristic	Characteristic	Characteristic
		diameter x	sectional area	yield moment	withdrawal	head pull-	tensile
		length	A _h	$M_{v,k}$	parameter ^{a)}	through	capacity
		d x I	[mm²]	[Nmm]	$f_{ax,k}$	parameter ^{a)}	$f_{tens,k}$
		[mm]	,		[N/mm ²]	$f_{head,k}$	[kN]
						[N/mm²]	
3,1 x !	90	2,98 x 89	30,2	4100	2,45	18,81	NPD ^{b)}

- a) Parameter was measured on timber with a characteristic density of 350 kg/m3 (C24)
- b) No Performance Determined





Page 3 / 3 DoP 011 Version 6.0

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Eura, 28th August 2015

Tuomas Pere, Managing Director

Twoms Pen